©OUTLANDER™ XT™

HIGHLIGHTS

- Rotax® V-twin engine options
- New arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 3,000-lb (1,361 kg) WARN[†] winch with roller fairlead
- Heavy-duty front and rear bumpers
- Handlebar wind deflectors

Power Steering

- · Painted plastics for premium look
- 14-in. cast-aluminum wheels
- 26-in. ITP† Terracross radial tires
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control

- Torsional Trailing arm Independent (TTI) rear suspension
- 625-W magneto

Tri-Mode Dynamic Power Steering (DPS)

- High-strength, multifunction racks with LinQ[™] quick-attach accessory system
- 5.7-gal (21.4 L) water-resistant rear compartment



	Iron Grey and Octane Blue / 650 / 1000F
--	---

with Geometric Control		Itoh diey and ootahe blac / 000 / 1000k		
ENGINES	650	1000R	TIRES / WHEELS	
Туре	62 hp, Rotax 649.6 cc V-twin, liquid cooled	91 hp, Rotax 976 cc V-twin, liquid cooled	Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Fuel Delivery System		Intelligent Throttle Control (iTC™) with Electronic Fuel Injection	Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
		(EFI)	Wheels	14-in. cast-aluminum
Transmission	CVT, P / R / N / H / L, standard engine braking			
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential		DIMENSIONS / CAPACITIES	

SUSPENSIONS			
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel		
Front Shocks	Oil		
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel		
Rear Shocks	0il		

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

LxWxH	86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	11 in. (27.9 cm)
Seat Height	34.5 in. (87.7 cm)
Engine / Dry Weight*	650: 749 lb (341 kg) 850: 800 lb (363 kg) 1000R: 826 lb (375 kg)
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES				
Gauge	Multifunction digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour	4.5-in. digital display: Speedometer, tachometer, odometer, trip & hour meters,gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
			Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
	meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock		Seat	Standard
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front & rear bumpers, handlebar wind deflectors, mudguards			

WARRANTY

Factory 2-years limited warranty

©2019 Bombardier Recreational Products Inc (BRP), All rights reserved, TM, ® and the BRP logo are registered trademarks of BRP or its affiliates, Products are distributed in the U.S.A. by BRP US Inc. "Base model dry weight shown. "Visco-Lok is a trademark of GKN Viscodrive GmbH. 'All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation, Ride responsible, BRP highly recommends that all AIV drivers take a training course, for safety and training information, see your dealer or, in U.S.A. call the AIV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

